

Hugo Kangaroo Pocket Hoodie

Relaxed raglan hoodie with lined three-piece hood and kangaroo pocket review draft

Garment Type: Pullover Hoodie | Difficulty: Confident Beginner | Provenance: FreeSewing | License: MIT / CC BY 4.0

PRINTER CALIBRATION & SCALE VERIFICATION

Measure both test squares with a rigid ruler before cutting fabric. Print at 100% scale without shrinking.



- Scale Rules:
- 1. Open in Acrobat Reader
 - 2. Select Actual Size 100%
 - 3. Do NOT Fit to Page
 - 4. Verify dimensions above

SIZE SELECTION & EASE RECOMMENDATIONS

Select by chest measurement. Hugo is drafted for relaxed layering; compare the finished chest and length before cutting.

+18 cm positive ease at the chest in this fixed-size review adaptation.

STANDARD BODY MEASUREMENTS CHART

Size Range	XS	S	M	L	XL	2XL	3XL
Full Bust/Chest	80 cm	86 cm	92 cm	98 cm	108 cm	118 cm	128 cm
Full Hip / Seat	88 cm	94 cm	100 cm	106 cm	116 cm	126 cm	136 cm

FINISHED MEASUREMENTS & MATERIALS

FINISHED GARMENT MEASUREMENTS (INCLUDES DESIGN EASE)

Dimension	XS	S	M	L	XL	2XL	3XL
Finished Chest	98 cm	104 cm	110 cm	116 cm	126 cm	136 cm	146 cm
Hem Sweep	102 cm	108 cm	114 cm	120 cm	130 cm	140 cm	150 cm
Garment Length	72 cm	74 cm	76 cm	78 cm	80 cm	82 cm	84 cm

FABRIC REQUIREMENTS (45 IN / 115 CM & 60 IN / 150 CM BOLTS)

Bolt Width	XS	S	M	L	XL	2XL	3XL
45" / 115 cm Fabric	2.4 yd	2.4 yd	2.4 yd	2.85 yd	2.85 yd	3.3 yd	3.3 yd
60" / 150 cm Fabric	1.95 yd	1.95 yd	1.95 yd	2.3 yd	2.3 yd	2.75 yd	2.75 yd

RECOMMENDED FABRICS & STRETCH PROPERTIES

Recommended Substrates: French terry, sweatshirt fleece, or heavy cotton jersey, Rib knit for cuffs and hem band. Stretch Requirement: 20-40% Stretch.

NOTIONS & SEWING TOOLS CHECKLIST

- ☐ Matching all-purpose polyester or cotton sewing thread
- ☐ Universal sewing needle size 80/12
- ☐ Ballpoint or jersey needle size 80/12
- ☐ Cotton drawcord 1.2 m
- ☐ Herringbone twill tape for neck seam
- ☐ Sharp fabric shears
- ☐ Measuring tape
- ☐ Iron and pressing ham

PATTERN INVENTORY & CUTTING LAYOUT

STANDARD SEAM & HEM ALLOWANCES

Use the seam and hem allowances printed on each pattern piece. Verify every allowance label before cutting fabric.

PATTERN PIECE INVENTORY & CUTTING SCHEDULE

Piece Name	Cut Quantity	Material / Interfacing
Hoodie Front Body	Cut 1 on Fold	Main Fabric
Hoodie Back Body	Cut 1 on Fold	Main Fabric
Raglan Sleeves	Cut 1 Pair	Main Fabric
Crossover Hood Panels	Cut 2 Outer Pairs, Cut 2 Lining Pairs	Main Fabric
Hood Centre Panels	Cut 1 Outer, Cut 1 Lining	Main Fabric
Neck Binding	Cut 1 in Rib Knit	Main Fabric
Kangaroo Pocket	Cut 1 on Fold	Main Fabric
Pocket Facings	Cut 2 Mirrored	Main Fabric
Rib Wrist Cuffs	Cut 1 Pair in Rib Knit	Main Fabric
Rib Hem Waistband	Cut 1 on Fold in Rib Knit	Main Fabric

FABRIC PREPARATION & CUTTING RULES

- Press fabric before cutting to remove packing folds and pre-shrink fibers.
- Align piece grainlines strictly parallel to fabric selvages.
- Transfer notch markings with small 3 mm snips into the seam allowance margin.

MULTI-PAGE TILE ASSEMBLY INSTRUCTIONS

1. Check Sheet 1 calibration square before printing the remaining pattern sheets.
2. Trim right and bottom border lines along the dashed perimeter frame.
3. Match corner crosshairs, such as A1 to A2 and B1 to B2, without overlapping.
4. Tape sheets securely on both sides before cutting paper pieces.

STEP-BY-STEP SEWING INSTRUCTIONS

Step 1: Reinforce the Kangaroo Pocket Openings

Stabilize the marked ends of both diagonal hand openings, turn the opening allowances to the wrong side, and topstitch them. Press the remaining Kangaroo Pocket edges under, align its center fold and placement marks with the Hoodie Front Body, then topstitch the sides and lower edge with reinforced stitching at all four opening ends.

Step 2: Attach Raglan Sleeves

Match each Raglan Sleeve to the front body at the single-notch seam and to the back body at the double-notch seam, right sides together. Stitch all four raglan seams with a stretch-compatible stitch, finish the allowances together, and press them toward the sleeves.

Step 3: Close Underarm and Body Seams

Fold the hoodie right sides together and match the raglan seam intersections. Stitch continuously from each sleeve wrist through the underarm and down the body side seam. Finish the allowances together and press them toward the back.

Step 4: Assemble the Lined Crossover Hood

Stitch the shell hood center-back seam and repeat for the lining. Place shell and lining right sides together, stitch the face opening, turn and press, then topstitch the marked drawcord casing. Work the drawcord through the casing before attaching the hood.

Step 5: Attach Hood to Neckline

Overlap the crossover hood fronts at the center-front notch and baste the overlap. Match the hood center back to the body center back, pin the hood to the neckline right sides together, stitch, and cover the finished seam allowance with herringbone twill tape.

Step 6: Attach Rib Cuffs and Hem Band

Join the Rib Wrist Cuffs and Rib Hem Waistband into separate loops, then fold each loop lengthwise wrong sides together. Quarter-mark every band and opening; stretch the rib evenly while attaching the cuffs and waistband with a stretch-compatible stitch.

TROUBLESHOOTING & PRO SEWING TIPS

Issue: Seams puckering along stitch line

Fix: Insert fresh needle and test balance on fabric scrap.

Issue: Wavy edge along curved perimeter

Fix: Staystitch immediately after cutting and use walking foot.