



German Everyday Raglanshirt

German Everyday Raglanshirt Verified open pattern specification

Garment Type: Everyday Raglanshirt | Difficulty: Beginner | Provenance: Threadline Open Design Studio | License: CC BY-SA 4.0

PRINTER CALIBRATION & SCALE VERIFICATION

Measure both test squares with a rigid ruler before cutting fabric. Print at 100% scale without shrinking.



- Scale Rules:
- 1. Open in Acrobat Reader
 - 2. Select Actual Size 100%
 - 3. Do NOT Fit to Page
 - 4. Verify dimensions above

SIZE SELECTION & EASE RECOMMENDATIONS

Select size based on full bust/chest measurement.
+4 to +8 cm positive wearing ease for comfortable drape.

STANDARD BODY MEASUREMENTS CHART

Size Range	XS	S	M	L	XL	2XL	3XL
Full Bust/Chest	80 cm	86 cm	92 cm	98 cm	108 cm	118 cm	128 cm
Full Hip / Seat	88 cm	94 cm	100 cm	106 cm	116 cm	126 cm	136 cm

FINISHED MEASUREMENTS & MATERIALS

FINISHED GARMENT MEASUREMENTS (INCLUDES DESIGN EASE)

Dimension	XS	S	M	L	XL	2XL	3XL
Finished Chest	86 cm	92 cm	98 cm	104 cm	114 cm	124 cm	134 cm
Hem Sweep	90 cm	96 cm	102 cm	108 cm	118 cm	128 cm	138 cm
Garment Length	62 cm	64 cm	66 cm	68 cm	70 cm	72 cm	74 cm

FABRIC REQUIREMENTS (45 IN / 115 CM & 60 IN / 150 CM BOLTS)

Bolt Width	XS	S	M	L	XL	2XL	3XL
45" / 115 cm Fabric	1.55 yd	1.55 yd	1.55 yd	1.75 yd	1.75 yd	2.1 yd	2.1 yd
60" / 150 cm Fabric	1.2 yd	1.2 yd	1.2 yd	1.4 yd	1.4 yd	1.75 yd	1.75 yd

RECOMMENDED FABRICS & STRETCH PROPERTIES

Recommended Substrates: Lightweight to medium-weight suitable fabric substrates, Pre-washed natural fibers cotton, linen, or bamboo. Stretch Requirement: None 0% stable woven.

NOTIONS & SEWING TOOLS CHECKLIST

- ☐ Matching all-purpose polyester or cotton sewing thread
- ☐ Universal sewing needle size 80/12
- ☐ Sharp fabric shears
- ☐ Measuring tape
- ☐ Iron and pressing ham

PATTERN INVENTORY & CUTTING LAYOUT

STANDARD SEAM & HEM ALLOWANCES

Use the seam and hem allowances printed on each pattern piece. Verify every allowance label before cutting fabric.

PATTERN PIECE INVENTORY & CUTTING SCHEDULE

Piece Name	Cut Quantity	Material / Interfacing
Crew Tee Front	Cut 1 on Fold	Main Fabric
Tee Back Bodice	Cut 1 on Fold	Main Fabric
Short Sleeve	Cut 1 Pair	Main Fabric
Rib Neckband	Cut 1 in Rib Knit	Main Fabric

FABRIC PREPARATION & CUTTING RULES

- Press fabric before cutting to remove packing folds and pre-shrink fibers.
- Align piece grainlines strictly parallel to fabric selvages.
- Transfer notch markings with small 3 mm snips into the seam allowance margin.

MULTI-PAGE TILE ASSEMBLY INSTRUCTIONS

1. Check Sheet 1 calibration square before printing the remaining pattern sheets.
2. Trim right and bottom border lines along the dashed perimeter frame.
3. Match corner crosshairs, such as A1 to A2 and B1 to B2, without overlapping.
4. Tape sheets securely on both sides before cutting paper pieces.

STEP-BY-STEP SEWING INSTRUCTIONS

Step 1: Knit Preparation

Cut crew front bodice, back bodice, short sleeves, and rib knit neckband with stretch crosswise. Press seam allowances.

Step 2: Shoulder Seams

Sew shoulder seams with right sides facing using stretch stitch or 4-thread overlock. Press seam allowances.

Step 3: Attach Rib Neckband

Join short ends of rib neckband to form loop, fold lengthwise wrong sides together, and stitch evenly to neckline. Press seam allowances.

Step 4: Attach Sleeves

Insert short sleeves into armholes flat, matching front and back notches. Press seam allowances.

Step 5: Side Seams and Hems

Sew side seams and underarm seams in one continuous pass. Hem sleeves and lower hem with twin needle. Press seam allowances.

TROUBLESHOOTING & PRO SEWING TIPS

Issue: Seams puckering along stitch line

Fix: Insert fresh needle and test balance on fabric scrap.

Issue: Wavy edge along curved perimeter

Fix: Staystitch immediately after cutting and use walking foot.