



French Fluid Rayon Blouse

French Fluid Rayon Blouse Verified open pattern specification

Garment Type: Rayon Blouse | Difficulty: Confident Beginner | Provenance: Threadline Open Design Studio | License: CC BY-SA 4.0

PRINTER CALIBRATION & SCALE VERIFICATION

Measure both test squares with a rigid ruler before cutting fabric. Print at 100% scale without shrinking.



- Scale Rules:
- 1. Open in Acrobat Reader
 - 2. Select Actual Size 100%
 - 3. Do NOT Fit to Page
 - 4. Verify dimensions above

SIZE SELECTION & EASE RECOMMENDATIONS

Select size corresponding to full chest/bust measurement. Compare bicep circumference for comfortable sleeve fit.

Tailored shirts incorporate +10 to +14 cm chest ease for relaxed everyday movement and layering.

STANDARD BODY MEASUREMENTS CHART

Size Range	XS	S	M	L	XL	2XL	3XL
Full Bust/Chest	80 cm	86 cm	92 cm	98 cm	108 cm	118 cm	128 cm
Full Hip / Seat	88 cm	94 cm	100 cm	106 cm	116 cm	126 cm	136 cm

FINISHED MEASUREMENTS & MATERIALS

FINISHED GARMENT MEASUREMENTS (INCLUDES DESIGN EASE)

Dimension	XS	S	M	L	XL	2XL	3XL
Finished Chest	94 cm	100 cm	106 cm	112 cm	122 cm	132 cm	142 cm
Hem Sweep	102 cm	108 cm	114 cm	120 cm	130 cm	140 cm	150 cm
Garment Length	62 cm	64 cm	66 cm	68 cm	70 cm	72 cm	74 cm

FABRIC REQUIREMENTS (45 IN / 115 CM & 60 IN / 150 CM BOLTS)

Bolt Width	XS	S	M	L	XL	2XL	3XL
45" / 115 cm Fabric	1.85 yd	1.85 yd	1.85 yd	2.2 yd	2.2 yd	2.5 yd	2.5 yd
60" / 150 cm Fabric	1.55 yd	1.55 yd	1.55 yd	1.75 yd	1.75 yd	2.1 yd	2.1 yd

RECOMMENDED FABRICS & STRETCH PROPERTIES

Recommended Substrates: Cotton poplin, Oxford cloth, linen, or chambray. Stretch Requirement: None 0% stable woven.

NOTIONS & SEWING TOOLS CHECKLIST

- ☐ Matching all-purpose polyester or cotton sewing thread
- ☐ Universal sewing needle size 80/12
- ☐ 10 to 12 mm shirt buttons 8 to 10 count
- ☐ Lightweight fusible interfacing for collar and cuffs
- ☐ Sharp fabric shears
- ☐ Measuring tape
- ☐ Iron and pressing ham

PATTERN INVENTORY & CUTTING LAYOUT

STANDARD SEAM & HEM ALLOWANCES

Use the seam and hem allowances printed on each pattern piece. Verify every allowance label before cutting fabric.

PATTERN PIECE INVENTORY & CUTTING SCHEDULE

Piece Name	Cut Quantity	Material / Interfacing
Darted Front	Cut 1 Pair	Main Fabric
Back Bodice	Cut 1 on Fold	Main Fabric
Sleeve	Cut 1 Pair	Main Fabric
Collar Leaf	Cut 2 (1 Interfaced)	Main Fabric
Collar Stand	Cut 2 (1 Interfaced)	Main Fabric

FABRIC PREPARATION & CUTTING RULES

- Press fabric before cutting to remove packing folds and pre-shrink fibers.
- Align piece grainlines strictly parallel to fabric selvages.
- Transfer notch markings with small 3 mm snips into the seam allowance margin.

MULTI-PAGE TILE ASSEMBLY INSTRUCTIONS

1. Check Sheet 1 calibration square before printing the remaining pattern sheets.
2. Trim right and bottom border lines along the dashed perimeter frame.
3. Match corner crosshairs, such as A1 to A2 and B1 to B2, without overlapping.
4. Tape sheets securely on both sides before cutting paper pieces.

STEP-BY-STEP SEWING INSTRUCTIONS

Step 1: Bust Darts and Cutting

Cut darted front panels, back bodice on fold, sleeves, and collar pieces from fluid woven fabric.

Step 2: Bust Darts

Stitch bust darts on front bodice panels, pressing dart fullness downward.

Step 3: Shoulders and Collar

Sew shoulder seams. Construct collar and stand, attach to neckline, and enclose seam neatly inside inner stand.

Step 4: Set Sleeves

Set sleeves into armholes with right sides facing, easing sleeve cap into armhole.

Step 5: Side Seams and Hems

Stitch side seams and sleeve underarm seams, turn narrow double hem along bottom edge, and press.

TROUBLESHOOTING & PRO SEWING TIPS

Issue: Seams puckering along stitch line

Fix: Insert fresh needle and test balance on fabric scrap.

Issue: Wavy edge along curved perimeter

Fix: Staystitch immediately after cutting and use walking foot.